

## SIMPLICITY

VEGAS



HOLLYWOOD



ATLANTE II



DRAKKAR ECO



## EFFICIENCY

DRAKKAR II



CALYPSO



KOURSK II 70



KOURSK II 90



## TECHNICAL

CALYPSO PRO



KOURSK II 70 PMMA  
KOURSK II 90 PRO



PALTUS



NAVY



DRAKKAR ECO META



## Simplicity

Luminaire all in one. Efficient, reliable and easy to install, suitable for all budget.  
Deliver with automatic cable gland.

REFERENCE	MATERIAL	CONNECTOR	IK	IP	LUMEN (LM)	LM/W
VEGAS	PC	DL06 FAST C.G.	08	66	2300-5800	119
HOLLYWOOD	PC/PC	DL01 FAST C.G.	09	65	2750-6350	115
ATLANTE II	PC/SS304	GENRAD FAST C.G.	10	69K	2600-7000	140
DRAKKAR ECO	PC/ABS	DL06 FAST C.G.	09	65	1800-6000	104

## Efficiency

Luminaire with low energy consumption & 5y warranty. Suitable for technical, industrial or architectural application.  
Deliver with automatic cable gland or 1.5m 3G1.5 cable.

REFERENCE	MATERIAL	CONNECTOR	IK	IP	LUMEN (LM)	LM/W	UGR	BEAM ANGLE
DRAKKAR II	PC/PC	GENRAD FAST C.G.	10	66	2500-8000	140	<26	120
CALYPSO	PC/ALU	GENRAD FAST C.G.	10	66	3800-9800	130	<26	120
KOURSK II 70	PC/SS316	1.5m H07RNF 3G1.5	10	69K	2150-5600	131	<22 / <25	40 / 90 / 120 / DASY / ASYM
KOURSK II 90	PC/SS316	1.5m H07RNF 3G1.5	10	69K	3100-8200	140	<26	140

## Technical

Robust luminaire, with long life time and warranty up to 7y. Suitable for industry with critical environment, extreme temperature, food industry and jail. Deliver with automatic cable gland or 1.5m 3G1.5 cable.

REFERENCE	MATERIAL	CONNECTOR	IK	IP	LUMEN (LM)	LM/W	TA °C	LIFE TIME
CALYPSO PRO	PC/ALU	CONRAD FAST C.G.	10	66	7900-9800	126	-40/+45	70000hrs
KOURSK II 70 PMMA	PMMA/SS316L	1.5m H07RNF 3G1.5	09	69K	2150-5250	120	-35/+45	80000hrs
KOURSK II 90 PRO	PC/SS316L	1.5m H07RNF 3G1.5	10	69K	3200-8960	140	-40/+45 ++	100000hrs
PALTUS	PC/ALU	C.G.	10+	66	3250-8450	130	-25/+35	70000hrs
NAVY	Glass/SS304	C.G.	07	65	4900-10500	140	-30/+35	50000hrs
DRAKKAR ECO META	PMMA/ABS	1.5m H07RNF 3G1.5	10	66	1800-6000	104	-10/+35	50000hrs

## MANAGING INTERFACE

Save energy and optimised the power consumption & lumen output.  
Built-in our product or deported. Wired or wireless solutions.

Standard solution built-in :

- Motion HF sensor, PIR sensor
- DALI DT6-DT8, 1-10V, Casambi protocol

Standard solution deported :

- ZIGBEE, module BLE gateway
- PIR sensor
- TOUCH series switch



## Integrated solution vs Product code

REFERENCE	DALI	1-10V	HF ON/OFF	IR ON/OFF	HF DALI	IR DALI	HF 1-10V	IR 1-1V	BLE	CENTRIC
VEGAS	-	-	-	-	-	-	-	-	-	-
HOLLYWOOD	-	-	-	-	-	-	-	-	-	-
ATLANTE II	BEGA	GRA	-	-	-	-	-	-	-	-
DRAKKAR ECO	BEGA	GRA	-	DETI	-	-	-	GRAM	-	-
DRAKKAR II	BEGA	GRA	DET	DETI	BEGH	BEGM	PRE	GRAM	BLE	-
KOURSK II 70	BEGA	GRA	-	-	-	-	-	-	-	TNW
KOURSK II 90	BEGA	GRA	DET	-	BEGH	-	-	-	BLE	-
CALYPSO PRO	BEGA	GRA	-	-	-	-	-	-	-	-
KOURSK II 70 PMMA	BEGA	GRA	-	-	-	-	-	-	-	-
KOURSK II 90 PRO	BEGA	GRA	-	-	-	-	-	-	-	-
PAULTUS	BEGA	GRA	DET	-	-	-	-	-	-	-
NAVY	BEGA	GRA	-	-	-	-	-	-	-	-
DRAKKAR ECO META	BEGA	GRA	DET	DETI	-	-	PRE	GRAM	-	-